

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously presented) A multi-port receptacle comprising:
 - a monolithic housing defining at least two ports, each port including:
 - first end defining an opening for receiving a module;
 - a second end defining a wall;
 - a passageway formed between the first end and the second end;
 - a base having a cut-out portion adjacent the second end; and
 - an electrical connector mountable within the second end, the electrical connector disposed within the cut-out portion of the base so that upon mounting of the multi-port receptacle to a motherboard the electrical connector is colinear with the passageway.
2. (Previously presented) The multi-port receptacle assembly of claim 1, wherein the base is formed by a plate extending and enclosing approximately an entire side of the housing.
3. (Previously presented) The multi-port receptacle assembly of claim 1, wherein the base includes first mounting features for latching to corresponding second mounting features of the housing.
4. (Previously presented) The multi-port receptacle assembly of claim 1 comprising the housing injection molded of plastic.
5. (Previously presented) The multi-port receptacle assembly of claim 1, wherein the base is formed of a metal plate.
6. (Previously presented) A multi-port receptacle of claim 1, wherein the ports include a first mounting guide and the electrical connector includes a second mounting guide to

correspondingly engage the first mounting guides in order to mount the electrical connector within the ports.

7. (Previously presented) A multi-port receptacle of claim 1, wherein the base includes a ejection spring support at the second end having the cut-out formed therein.

8. (Previously presented) The multi-port receptacle assembly of claim 7, wherein the contacts of the electrical connector are generally coplanar with the cutout and a major surface of the base.

9. (Previously presented) A multi-port receptacle assembly of claim 8, wherein the ejection spring support includes ground tabs protruding into the passageway of the port.

10. (Previously presented) The multi-port receptacle of claim 1, wherein the housing is metalized.

11. (Previously presented) The multi-port receptacle assembly of claim 1, wherein the housing is plated.

12. (Previously presented) The multi-port receptacle assembly of claim 1, wherein the base is segmented by a group of at least six first mounting features forming a perimeter of each segment and a plurality of second mounting features of the housing corresponding to the first mounting features in order to securely attach the housing and base together.

13. (Previously presented) A method of assembling a multi-port receptacle comprising the steps of:

providing a base having a first mounting feature;

providing a monolithic housing that defines at least two ports and including a second mounting feature, a first end and a second end;

mounting an electrical connector within the second end of each port; and

mounting the housing to a base having the first mounting feature mated to the second mounting feature of the housing.

14. (Previously presented) The method of claim 13, wherein the electrical connector is slidingly engaged within each port of the housing along mounting guides protruding within the port.

15. (Previously presented) The method of claim 13 including the step of inserting the base horizontally along the passageway of each port so that a ejection spring support of the base having a cutout slides over the electrical connector mounted therein.

16. (Previously presented) The method of claim 15, wherein the ejection spring support of the base is received within a gap defined between the electrical connector and the second end of the housing.

17. (Previously presented) The method of claim 15 further comprising the steps of inserting the base vertically into each port so that the first mounting features latch with the second mounting features.

18. (Previously presented) The method of assembling a multi-port receptacle of claim 15, wherein the first mounting feature is a tab protruding perpendicularly from the base and the second mounting feature is a boss protruding from the side of the housing.

19. (Previously presented) The method of assembling a multi-port receptacle of claim 15 further comprising the steps of mounting the assembled multi-port receptacle assembly to a motherboard where mounting pegs on the base of the multi-port receptacle assembly are aligned and mounted to holes in a motherboard simultaneously with the alignment of contact tails of the electrical connector to the motherboard.

20. (Previously presented) The method of assembling a multi-port receptacle of claim 15 further comprising the steps of placing a bezel over the first end of the housing which forms a nose

having ground tabs to mechanically and electrically abut the bezel in order to assist in an electrical connection in order to provide a portion of the housing of the multi-port receptacle assembly at the same ground potential as the bezel.

21. (Previously presented) An integral multi-port module receptacle and motherboard assembly comprising:

a monolithic housing forming at least two ports, each port including a first end for receiving a module therein, a second end having an electrical connector and a passageway formed between the first end and the second end and each port is formed on at least three sides by walls formed by the housing and on a fourth side by a base plate, wherein the base plate includes an aperture in which the electrical connector is disposed.

22. (Previously presented) The assembly of claim 21, wherein the port includes a pair of mounting guides and the electrical connector includes a pair of channels on the sides of the electrical connector for slidably engaging the pair of mounting guides.

23. (Previously presented) The assembly of claim 21, wherein the aperture is formed by a cut-out in the base plate.

24. (Previously presented) The assembly of claim 21, wherein the receptacle only has $2 + n$ parts where n is the number of ports.

25. (Previously presented) A multi-port receptacle comprising:

a monolithic housing defining at least two ports, each port including:

first end defining an opening for receiving a module;

a second end defining a wall;

a passageway formed between the first end and the second end;

a base having a cut-out portion adjacent the second end for receiving an electrical connector therein and the base having a plurality of mounting pins protruding from the base for mounting the base to a motherboard; and

the housing attached to the base.

26. (Previously presented) The multi-port receptacle of claim 25, wherein the base includes first mounting features for latching to corresponding second mounting features of the housing.

27. (Previously presented) The multi-port receptacle of claim 25, wherein the electrical connector is mounted within the cut-out portion prior to mounting the multi-port receptacle to the motherboard.